

Ddev Plastiks Industries Limited

TECHNICAL DATASHEET

SODIUM FILLER GRADE -AFSDF

TRANSPARENT FILLER MASTER BATCH COMPOUNDS IS BASED OF SODIUM SULFATE Na_2SO_4 PRODUCE FOR ALL LDPE FILMS, LLDPE FILMS, PE APPLICATION, PP SHEET/BOARDS AND INJECTION MOULDING PRODUCTS.

IT CAN GREATLY REDUCE THE PRODUCT COST AND MAINTAINED TRANSPARENCY AND OTHER PERFORMANCE OF THE FINAL PRODUCTS.

THE PRODUCTS MADE WITH IT IS JUST LOOKS AS SAME AS THAT WITH VERGINE POLYMERS WITHOUT DISTURBING TRANSPARENCY OF PRODUCTS.

Technical properties:

Transparent inorganic content 78+-1%

Appearance (Surface color) : White

Additives : Dispersion agent, processing aid

Processing temperature : 140 – 150 oC

Usage rate : 10 -20 %

Pellet Size : 3x3 (± 0.3) mm

Carrier resin: LLDPE

Compatibility: LDPE, LLDPE, HDPE.

Packing : 25 kgs per PE bag.

Storage : Keep at dry condition.

(The information given in the document is believed to be reliable and is given in good faith but without warranty. The user should test the product to assertion the suitability for intended use. The product specification or the whole document is subject to change without any prior notice.)